



Foster Milano Cucinotta Range 48" 4 burners inLine

Ranges

Code: 7154 900

AISI 304 Stainless steel

Satin finish

Enamelled cast iron grid

Solid metal knobs



DETAILS

Series Foster Milano

Finish Foster brushed

Material AISI 304 stainless steel

Texture Satin

OVEN SPECIFICATIONS

Oven type Multifunction Pyrolytic Oven

Cooking Functions 12

Control type Electronic

Temperature control Electronic

Commands 2 knobs / 6 touch keys

Language English

Cavity

Usable capacity 4.1CuFt

Cavity finish Dark gray pyrolitic enamel

Rack positions 6

Lighting Triple asimmetrical halogen (20W) lighting

Broil upper heating element 3,500 W (240 V)

Upper aux element 1,032 W (240 V)

Concealed bake lower heating element 3,000 W (240 V)

Convection element 2 x 1,300 W (240 V)

Door

Door Glasses 4 heat resistant glasses

Inner side Full glass

Hinges Heavy duty Steady Tilt

Handle Satin finish Stainless steel handle

Special features

Cleaning function Pyrolitic self clean

Probe T control Yes

Preset/last used temperature memory Yes

Preheat bar (25%, 50%, 75%, 100%) Yes

Automatic fast preheat Yes

Sabbath mode Yes

Safety Keyboard lock, Child door lock

Temperature unit °C/°F

Clock format 12/24 Hours

Delivered accessories

Chromed racks 2

Telescopic chromed rack 1

Enamelled grill set 1

Meat Probe 1

Technical Specifications

Electric supply 120/240VAC – 60Hz // 120/208VAC – 60Hz

Max Amp usage, power rating (240V,60Hz) 16.9 A – 3.84 Kw

Max Amp usage, power rating (208V,60Hz) 17.5 A – 3.54 Kw

Cable + conduit Yes

Plug No

Certification US & CA (ETL)

Warranty 24 months

Cooking Functions Pyrolitic Sel Clean with automatic door lock, Dual convection Bake, convection Broil, Convection Roast, Lower Convection (Pizza function), Bake, Broil, Delicate cooking, Defrost, Proof warm, Keep warm (warm plus), Light, Fast preheating

RANGETOP SPECIFICATIONS

Model Milano Rangetop 4B Line – 48" x 27"

Dimensions 47 ^{7/8}" x 27 "

Finish Satin finish

Grids Enamelled cast iron

Cooktop controls Knobs

Knobs Solid Metal

Safety Safety valves

Total power Btu 39,600 Btu/h

Burners 4

DC 15,500 Btu/h

Rapid 10,750 Btu/h

Semirapid 9,100 Btu/h

Auxiliary 5,000 Btu/h

Simmer ring 2

Simmer Rate 900

Technical requirements

Electrical supply 120V 60Hz

Gas std setting Natural Gas

LP Gas conversion Kit for all burners included


Delivered accessories (2x) bottle holder

(2x) st. steel spices container

Optional accessories Cast iron wok support

Notes: For technical details of oven and gas cooktop see below in "Equipment"

TECHNICAL DATA



EQUIPMENT



**Milano Rangetop 4 burners inLine
(with holder)**

3154 900



**Oven Milano single Stainless Steel
30"**

7168 900

OPTIONAL ACCESSORIES



Cast Iron Wok Support

9601 727

RECOMMENDED PAIRINGS



Cucinotta Hood 48"

2463 900