

Hood Cilindro wall



Hoods

Code: 2531 001



DETAILS


Material	AISI 304 stainless steel
Texture	Brushed in line
Chimney height	920 mm
Energy class	A+
Grease filters	1 grease filtres in stainless steel
Operation	Suction hood (filtering mode with optional carbon filters)
Air exhaust hole	ø 120/150 mm
Lighting	LED lighting: 4 x 1,2W (5.500 kelvin)
Motors	Brushless



Air flow rate	700mc/h
Motor power	160W
Hood type	Wall-mounted suction wood
Type of commands	Minimal electronic controls
Suction speed	4 operating speeds
Notes:	Fume exhaust ducts must have an internal diameter not lower than 120 mm
FEATURES	
Auto delayed shutdown	All the models with electronic interface can be programmed to turn off the suction at a postponed moment, so as to prolong the aeration of the room even after the cooking has been completed.
Brushless motor	State-of-the-art Brushless motors allow high air flow rates while maintaining a low energy consumption. Furthermore, they have an almost never-ending duration.
Led lighting	Particular attention to energy saving with LED lighting systems. They assure a 10 times lower consumption and a 10 times longer duration. Our LED lights are designed to create an adequate comfort and safety in the cooking area.
Steel filters	Where the filter is in plain sight, the aluminium filtering element is covered in stainless steel. This solution improves the look and increases the durability of the product.



TECHNICAL DATA






GALLERY




OPTIONAL ACCESSORIES




Carbon filter 9700 380



Collector for 2 pipes 2523 000



Collector for 3 pipes 2524 000



Collector for 4 pipes 2525 000



Flexible silencing canalization 9700 602



Flexible silencing canalization 9700 603