



Hood KS

Hoods

Code: 2406 002

60 cm



DETAILS


Material	Stainless steel
Texture	Brushed in line
Chimney height	490 - 840 mm
Energy class	A
Product details	Telescopic chimney
Grease filters	Grease filtres: 3 filtres for 90 cm hood, 2 filtres for 60 cm hood
Operation	Suction hood (filtering mode with optional carbon filters)
Air exhaust hole	ø 120 mm
Lighting	LED lighting 2 x 1,2 W (4.000 kelvin)



Air flow rate	450mc/h
Motor power	125W
Hood type	Wall-mounted suction wood
Suction speed	3 operating speeds
Notes:	Fume exhaust ducts must have an internal diameter not lower than 120 mm
FEATURES	
Auto delayed shutdown	All the models with electronic interface can be programmed to turn off the suction at a postponed moment, so as to prolong the aeration of the room even after the cooking has been completed.
Led lighting	Particular attention to energy saving with LED lighting systems. They assure a 10 times lower consumption and a 10 times longer duration. Our LED lights are designed to create an adequate comfort and safety in the cooking area.



TECHNICAL DATA






GALLERY




OPTIONAL ACCESSORIES




Carbon filter



Collector for 2 pipes



Collector for 3 pipes



Collector for 4 pipes



Flexible silencing canalization



Flexible silencing canalization