

Cooker hob Power



Gas hobs
Code: 7018 032



DETAILS

Type	Gas Hob
Material	AISI 304 stainless steel
Texture	Brushed in line
Finish	Foster brushed
Edge/Installation Type	Standard (8 mm Edge)
Heating element	Five burners
Base size	60 cm
Width	75 cm
Dimensions	750x500 mm

Built-in hole	560 x 480 mm
---------------	--------------

Supply	220 - 240 V; 50/60 Hz
--------	-----------------------

Total power	10.950 W
-------------	----------

Auxiliary	1.000 W
-----------	---------

Semirapid	1.750 W + 1.400 W (reduced)
-----------	-----------------------------

Rapid	2.800 W
-------	---------

Double crown	4.000 W
--------------	---------

Grids	Cast iron grids and enamelled burner covers
-------	---

Gas type	Tested for installation with natural gas, LPG nozzle set included.
----------	--

Ignition	Electric ignition under knob
----------	------------------------------

Safety	Safety valve with quick-acting thermocouple
--------	---

FEATURES

Cast iron grids	Cast-iron is the ideal material for an hob grid, this due to the manifold properties characterising it: high heat capacity that improves cooking performance; high weight and stability that improve safety; sturdiness that preserves the hob's original aspect over time; easy cleaning.
-----------------	--

Safe cooking	All Foster cooker hobs are equipped with safety valves. They shut off the gas supply very quickly if the flame accidentally goes out.
--------------	---

Special burners

Many Foster hobs are equipped with special burners, with two or three rings of fire that greatly increase the power delivered and the heated surface. In the DUAL models the two fire crowns also have independent ignition, making these burners perfect for both intensive and delicate cooking.

Under-knob ignition

The utmost freedom of movement with electronic under-knob ignition, a common feature of all models that allows a one-hand ignition of the burner.

Narrow cut-out

These 5 burners products for standard built-in installation require a cut-out of only 56 cm, i.e. less than their nominal width. This makes them an interesting alternative for 60 cm models, which usually require the same cut-out.

TECHNICAL DATA

